










1" x 17,02 mm**25,4 x 17,02 mm****Roller 15,88 mm****16B - 1 - 2 - 3****B1 B2 B3 b1 C r3**

16,2 47,7 79,6 15,8 2,5 26

**1****2****3****4****5****6****7****8****Material: C45 steel / * Material: EN-GJL-200 cast iron**

Z	de	dp	simple					double					triple						
			dm	A	Compass	Type	Kg.	dm	A	Compass	Type	Kg.	dm	A	Compass	Type	Kg.		
13	117,7	106,13	73	38	1615	1	0,98												
14	125,7	114,15	75	38	1615	1	1,14												
15	133,7	122,16	76	38	1615	1	1,30		47,7	2012	3	2,11							
16	141,8	130,20	90	32	2012	1	1,40		47,7	2517	3	2,25							
17	149,8	138,23	90	32	2012	1	1,59		47,7	2517	3	2,53		79,6	2517	5	4,29		
18	157,8	146,28	108	44	2517	1	2,10		47,7	2517	3	3,10							
19	165,9	154,31	108	44	2517	1	2,29		47,7	2517	3	3,80		79,6	3030	5	4,36		
20	173,9	162,38	110	44	2517	1	2,60		47,7	2517	3	4,10							
21	182,0	170,42	110	44	2517	1	2,81		140	51	3020	2	4,15		79,6	3030	5	6,69	
22	190,1	178,48	110	44	2517	1	3,10		140	51	3020	2	4,90						
23	198,1	186,53	110	44	2517	1	3,38		140	51	3020	2	5,69		159	89	3535	4	7,80
24	206,2	194,59	110	44	2517	1	3,70		140	51	3020	2	6,00						
25	214,2	202,66	110	44	2517	1	3,97		140	51	3020	2	6,38		175	89	3535	4	10,93
26	222,3	210,72	110	44	2517	1	4,26		140	51	3020	2	7,80						
27	230,4	218,79	110	44	2517	1	4,55		140	51	3020	2	9,27		175	89	3535	4	14,06
28	238,4	226,85	110	44	2517	1	5,26		140	51	3020	2	11,40						
30	254,6	242,99	120	44	2517	1	5,97		140	76	3030	2	13,50		175	89	3535	4	19,10
38	319,2	307,59	160	51	3020	1	8,73		*160	76	3030	7	14,94		*175	89	3535	8	21,65
45	377,9	364,12	160	51	3020	1	12,49		*160	76	3030	7	19,80		*175	89	3535	8	28,10
57*	474,9	461,07	160	51	3020	6	13,87		175	89	3535	7	22,00		216	102	4040	8	40,50
76*	628,4	614,65	160	51	3020	6	22,63		175	89	3535	7	37,00		216	102	4040	8	53,30