




3/4" x 7/16"
19,05 x 11,68 mm
Roller 12,07 mm
12B - 1 - 2 - 3

B1 B2 B3 b1 C r3


11,1 30,3 49,8 10,8 2 19




1




2




3




4




5



6



7



8

Material: C45 steel / * Material: EN-GJL-200 cast iron

Z	de	dp	simple					double					triple						
			dm	A	CompassType	Kg.		dm	A	CompassType	Kg.		dm	A	CompassType	Kg.			
13	87,8	79,60	60	25	1210	1	0,35												
14	93,8	85,61	67	25	1610	1	0,40												
15	99,8	91,62	70	25	1610	1	0,44		30,3	1610	3	0,68		49,8	1615	5	1,11		
16	105,8	97,65	71	25	1610	1	0,53		30,3	1610	3	0,89							
17	111,9	103,67	76	25	1610	1	0,66		30,3	1610	3	1,14		49,8	1615	5	1,75		
18	117,9	109,71	90	32	2012	1	0,86		90	32	2012	2	1,18						
19	123,9	115,73	90	32	2012	1	0,94		90	32	2012	2	1,24		49,8	2012	5	1,99	
20	130,0	121,78	90	32	2012	1	1,04		108	44	2517	2	1,40						
21	136,0	127,81	102	44	2517	1	1,24		108	44	2517	2	1,68		49,8	2517	5	2,09	
22	142,0	133,86	108	44	2517	1	1,60		108	44	2517	2	1,99						
23	148,1	139,90	108	44	2517	1	1,70		108	44	2517	2	2,24		49,8	2517	5	3,00	
24	154,1	145,94	108	44	2517	1	1,81		108	44	2517	2	2,54						
25	160,2	151,99	108	44	2517	1	1,93		108	44	2517	2	2,87		49,8	2517	5	3,98	
26	166,2	158,04	108	44	2517	1	2,04		108	44	2517	2	3,17						
27	172,3	164,09	108	44	2517	1	2,14		108	44	2517	2	3,55		140	51	3020	4	3,90
28	178,3	170,13	108	44	2517	1	2,37		108	44	2517	2	4,10						
30	190,4	182,24	108	44	2517	1	2,60		108	44	2517	2	4,62		140	51	3020	4	5,64
38	238,9	230,69	108	44	2517	1	3,93		140	51	3020	2	8,11		140	51	3020	4	11,58
45	283,2	273,10	124	44	2517	1	5,52												
57*	355,9	345,81	124	44	2517	6	6,48		160	51	3020	7	10,28		160	51	3020	8	13,23
76*	471,1	460,99	124	44	2517	6	9,71		160	51	3020	7	15,24						